




ALMA M LTD.

SE TROUVE DANS CES COULEURS:



CARBONE - OR



CARBONE BLEU- DORÉ
(BRILLANT)



ROSA- MARBRE (BRILLANT)

SPÉCIFICATIONS ET OPTIONS

CADRE	Orbea Alma Carbon OMX, Boost 12x148, PF BB, Internal cable routing.
FOURCHE	Orbea Spirit Rigid Carbon 15x110
	Fox 32 Float SC Factory 100 FIT4 Remote PTU QR15x110 Kashima
PLATEAU DE PEDALIER	SRAM XX1 Eagle Dub Grey Boost 34t
DIRECTION	Acros 1-1/8 - 1-1/2" Semi-intergated Block Lock
CINTRE	OC3 Carbon Flat 31.8mm 760mm
POTENCE	OC3 31.8mm interface -8°
MANETTES	SRAM XX1 Eagle AXS
FREINS	SRAM Ultimate Carbon Stealth-a-majig Black Hydraulic Disc
	Shimano XTR M9100 Hydraulic Disc
PIGNON	SRAM XX1 XG-1299 Eagle 10-50t 12-Speed Rainbow
DERAILLEUR ARRIÈRE	SRAM XX1 Eagle AXS
CHAÎNE	SRAM XX1 Eagle 12-Speed rainbow
ROUES	DT Swiss XRC-1200 Spline 30c TLR 15/110mm CL
PNEUS	Maxxis Rekon 2.35" 120 TPI Exo TLR
PEDALE	N/A
TIGE SELLE	OC2 Carbon 27.2 Offset 0
	OC2 Dropper 27.2mm 80mm travel
SELLE	Selle Italia SLR Boost Fill Carbon Keramic Rail Ø7 x 9 mm
GUIDE-CHAÎNE	Orbea Alma Carbon OMR & OMX. Compatible up to 36T
BATTERIE	SRAM Powerpack
--	

GÉOMÉTRIE

TAILLE	S	M	L	XL
1 - SEAT_TUBE	400	445	483	533
2 - TOP_TUBE	559	593	618	647
3 - HEAD_TUBE	90	100	110	125
4 - CHAIN_STAY			430	
5 - BB_HEIGHT			309	
6 - BB_DROP			61	
7 - WHEELBASE	1083	1118	1144	1175
8 - HEAD_ANGLE			68	
9 - SEAT_ANGLE			74.5	
10 - STANDOVER	693	729	749	819
11 - REACH	395	426	448	474
12 - STACK	593	602	612	625
13 - FORK_LENGTH			500.8	
14 - OFFSET			44	

ERGONOMIE

TAILLE	BIELLE	POTENCE	CINTRE
S	170	60	760
M	175	75	760
L	175	75	760
XL	175	90	760

* La dimension du guidon est centre-centre